

6455-C

FROZEN BEVERAGE FREEZER

Single flavor, Countertop, Gravity feed









Most Compact & Versatile

Two flavor countertop model for frozen beverage and smoothies

Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

Simple Control, Easy Operation

Simple and intuitive control system makes operation and viscosity adjustment easy, swift and more precise

Low Mix Indicator

Light turns "ON" at low mix to alert operator to add mix

See-through Dispensing Door

Clear dispensing door design makes product more attractive and serves as great marketing tool

Standby & Indicator

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight; Indicator light turns ON blue under Standby mode

Perfect solution for alcoholic and non-alcoholic frozen beverages in bars, restaurants, hospitals, schools and kiosks

Hopper Agitators

Maintain product consistency and prevent product separation

Self-closing Dispensing Valves

Automatically prevents product overflow after dispense

Safety Protections

- High pressure switch to prevent compressor overheating
- Thermal overload to protect from motor overheating

Light Box (Optional)

- Illuminates flavor cards to attract more business
- Changes color to indicate Low Mix and Standby

One-hand Operated Spinner (Optional)


- Adds ability to blend and offer more variaties of treats
- Allows for multi-tasking one-hand operation that helps increase productivity and reduce serving time






6455-C

FROZEN BEVERAGE FREEZER





SPECIFICATIONS

Flavors	2
Freezing Cylinders	2 x 3.8L / 4.0qt
Mix Hoppers	2 x 8.0L / 8.5qt
Output Capacity (250ml)	112 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb	
Net	146 / 325	
Shipping	166 / 369	
Volume	0.48 CBM / 17.10 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	476 / 18.7	520/20.5
Depth	651/25.6	853/33.6
Height	950 / 37.4	1090 / 42.9

Electrical	MFS	MCA	Power(kW)
220-240/50/1	15	13	2.0
220-240/60/1	15	13	2.1
110-115/60/1	20	16	1.6

 $\boldsymbol{\cdot}$ Above specifications are subject to change without notice

FEATURES	
Control Systems	Two, Mechanical
Refrigerated Hoppers	
Hopper Agitators	\checkmark
Standby Mode	
Auto Closing Dispensing Valves	~
Low Mix Indicator Light	
Low Mix Indicator Alarm	~
Standby Mode	ightharpoons
Standby Indicator Light	~
High Pressure Protection	ightharpoons
Thermal Overload Protection	

AVAILABLE OPTIONS	
Top Air Discharge Chute	
Spinner	
Light Box	\checkmark