

Camshelving® Elements Series

4-Shelf Mobile Starter Units

Shelf Plates with Camguard® antimicrobial

2 Post Heights (with Casters)

70" (1778 mm), 78" (1980 mm)

3 Shelf Widths

18" (460 mm), 21" (540 mm), 24" (610 mm)

3 Shelf Lengths

36" (910 mm), 42" (1070 mm),

48" (1220 mm)



• Starter Unit includes:

4 Mobile Posts without leveling feet, pre-assembled with Post Connectors and Wedges, 1 bag of 32 Mobile Traverse Dovetails (16 ea. A and B), Vented Shelf Plates (for 4 shelves), 8 Mobile Traverses, Premium or Standard Casters (2 Swivel with Brake and 2 Swivel with no Brake) and instructions.

Features & Benefits

Strong Technology

Posts and Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up to 60" (1530 mm) long hold up to 900 lbs. per unit of evenly distributed static weight. Mobile traverse features a 45° gusset for maximum cross stabilization.

Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

Shelving for Life

Non-corrosive design will endure all areas of operation, dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

Requires Minimal Assembly

Can be put together with the use of a rubber mallet. Two-piece Mobile Dovetails secure Mobile Traverses so they can be set easily into place.

Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments. Add a shelf to an existing unit by simply ordering the appropriate Mobile Shelf Kit.

Optional Accessories

Identification Tags clip easily onto traverses.

Divider bars to create a custom storage unit.

Premium Casters

Stainless steel with a non-marking polyurethane wheel. Recommended for use in wet areas or in walk-in refrigerators and freezers.

Standard Casters

Zinc plated with a non-marking polyurethane wheel. Recommended for use in dry storage areas.

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____



Mobile Four Shelf Unit with Vented Shelf Plates.

Click here to buy now!

Central®

RESTAURANT PRODUCTS

1-866-285-1252

Approvals



Camshelving® Elements Series

4-Shelf Mobile Starter Units

Shelf Plates with Camguard® antimicrobial

2 Post Heights (with Casters)

70" (1778 mm), 78" (1980 mm)

3 Shelf Widths

18" (460 mm), 21" (540 mm), 24" (610 mm)

3 Shelf Lengths

36" (910 mm), 42" (1070 mm), 48" (1220 mm)

• Starter Unit includes:

4 Mobile Posts without leveling feet, pre-assembled with Post Connectors and Wedges, 1 bag of 32 Mobile Traverse Dovetails (16 ea. A and B), Vented Shelf Plates (for 4 shelves), 8 Mobile Traverses, Premium or Standard Casters (2 Swivel with Brake and 2 Swivel with no Brake) and instructions.

Four Shelf Starter Units with Standard Casters

CODE	TRAVERSE IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
70" (1778 mm) Height 18" (460 mm) Width			
EMU183670	36" 910 mm	60.13 (5.92)	27,28 (0,17)
EMU184270	42" 1070 mm	64.67 (5.92)	29,33 (0,17)
EMU184870	48" 1220 mm	69.08 (5.92)	31,33 (0,17)
78" (1980 mm) Height 18" (460 mm) Width			
EMU183678	36" 910 mm	61.41 (5.92)	27,86 (0,17)
EMU184278	42" 1070 mm	65.95 (5.92)	29,91 (0,17)
EMU184878	48" 1220 mm	70.36 (5.92)	31,91 (0,17)
70" (1778 mm) Height 21" (540 mm) Width			
EMU213670	36" 910 mm	65.08 (7.39)	29,52 (0,21)
EMU214270	42" 1070 mm	70.37 (7.39)	31,92 (0,21)
EMU214870	48" 1220 mm	75.43 (7.39)	34,21 (0,21)
78" (1980 mm) Height 21" (540 mm) Width			
EMU213678	36" 910 mm	66.36 (7.39)	30,10 (0,21)
EMU214278	42" 1070 mm	71.65 (7.39)	32,50 (0,21)
EMU214878	48" 1220 mm	76.71 (7.39)	34,79 (0,21)
70" (1778 mm) Height 24" (610 mm) Width			
EMU243670	36" 910 mm	69.64 (8.49)	31,59 (0,24)
EMU244270	42" 1070 mm	75.45 (8.49)	34,22 (0,24)
EMU244870	48" 1220 mm	81.86 (8.49)	37,13 (0,24)
78" (1980 mm) Height 24" (610 mm) Width			
EMU243678	36" 910 mm	70.92 (8.49)	32,17 (0,24)
EMU244278	42" 1070 mm	76.73 (8.49)	34,81 (0,24)
EMU244878	48" 1220 mm	83.14 (8.49)	37,71 (0,24)

Donut Bumper

CODE	DESCRIPTION	DIAMETER IN. (MM)	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
Bumper				
CSHDDB	Donut Bumper	5" 127 mm	2.01 (0.05)	0,34 (0,001)

Bumper Case Pack: 4

CAMBRO
TRUSTED FOR GENERATIONS™

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, CA 92647-2056, U.S.A.
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____

Four Shelf Starter Units with Premium Casters

CODE	TRAVERSE IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
70" (1778 mm) Height 18" (460 mm) Width			
EMU183670P	36" 910 mm	60.13 (5.92)	27,28 (0,17)
EMU184270P	42" 1070 mm	64.67 (5.92)	29,33 (0,17)
EMU184870P	48" 1220 mm	69.08 (5.92)	31,33 (0,17)
78" (1980 mm) Height 18" (460 mm) Width			
EMU183678P	36" 910 mm	61.41 (5.92)	27,86 (0,17)
EMU184278P	42" 1070 mm	65.95 (5.92)	29,91 (0,17)
EMU184878P	48" 1220 mm	70.36 (5.92)	31,91 (0,17)
70" (1778 mm) Height 21" (540 mm) Width			
EMU213670P	36" 910 mm	65.08 (7.39)	29,52 (0,21)
EMU214270P	42" 1070 mm	70.57 (7.39)	31,92 (0,21)
EMU214870P	48" 1220 mm	75.43 (7.39)	34,21 (0,21)
78" (1980 mm) Height 21" (540 mm) Width			
EMU213678P	36" 910 mm	66.36 (7.39)	30,10 (0,21)
EMU214278P	42" 1070 mm	71.65 (7.39)	32,50 (0,21)
EMU214878P	48" 1220 mm	76.71 (7.39)	34,79 (0,21)
70" (1778 mm) Height 24" (610 mm) Width			
EMU243670P	36" 910 mm	69.64 (8.49)	31,59 (0,24)
EMU244270P	42" 1070 mm	75.45 (8.49)	34,22 (0,24)
EMU244870P	48" 1220 mm	81.86 (8.49)	37,13 (0,24)
78" (1980 mm) Height 24" (610 mm) Width			
EMU243678P	36" 910 mm	70.92 (8.49)	32,17 (0,24)
EMU244278P	42" 1070 mm	76.73 (8.49)	34,81 (0,24)
EMU244878P	48" 1220 mm	83.14 (8.49)	37,71 (0,24)

Architect Specs

Posts: Proprietary non-corrosive composite material.
Post Connectors: Glass Filled Polypropylene.
Mobile Traverses: Proprietary non-corrosive composite material.
Vented/Solid Shelf Plates: Reinforced polypropylene with Camguard® antimicrobial.
Divider Bars: Glass Filled Nylon.
Mobile Dovetails: Resin Nylon
Wedges: Resin Polypropylene

Optional Accessories

Identification Tag 6" CSID **Color:** White/Clear **Case pack:** 12 each
Identification Tag 3" CSID3 **Color:** White/Clear **Case pack:** 12 each
Divider Bar Angled EDBA **Color:** Speckled Gray **Case pack:** 4 each
Divider Bar Straight EDBS **Color:** Speckled Gray **Case pack:** 4 each

Standard Colors

Brushed Graphite (580)

Approvals



Components