

### Stationary - Add-On Units

#### 4 Shelf Units, Vented Shelf Plates only with Camguard™ antimicrobial

##### 2 Post Heights

64" (162,6 cm) and 72" (182,9 cm)

##### 3 Shelf Widths

18" (45,7 cm), 21" (53,3) and 24" (61 cm)

##### 5 Shelf Lengths

36", 42", 48", 54", 60" (91,4 cm, 106,7 cm, 121,9 cm, 137,2 cm, 152,4 cm)

##### • Add-On Unit includes:

- One Post Kit
- Four Vented Shelf Kits



### Features & Benefits

#### Versatile Storage

For use in any environment, indoors or outdoors, including walk-in coolers and freezers, dry storage, wet areas or front of the house display. Works in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C). Weldless and rust free.

#### Fits in Any Space

Units combine together in straight lines by sharing posts of existing units. Corner Connectors, made of reinforced nylon, connect units together in a 90° angle. Unique design maximizes valuable space and offers strength and stability. Simplify assembly and reduce costs by sharing posts of existing unit without the use of add-on clips or "S" hooks.

#### Easy to Clean

Camshelving shelf plates contain Camguard™ antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing. The traverses and post kits are smooth polypropylene so they can be wiped or steam cleaned. The traverses can be easily removed and washed in a conveyor dishwasher.

#### Easy to Assemble

Assembles in minutes with the use of a rubber mallet. Requires no bolts or nuts, clips or stainless steel connectors. Molded in dovetails on Posts ensure that Traverses set easily into place.

#### Strong as Steel

Posts and Traverses are made of a steel core coated with polypropylene. Uniquely engineered Post Connectors offer exceptional cross stabilization. Shelves up to 48" (121,9 cm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" - 72" (137,2 - 182,9 cm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold 400 lbs. (182 kg) for any length traverse.

#### Easy to Adjust

Requires use of rubber mallet. Shelves can be adjusted at 4" (10,2 cm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Sturdy reinforced nylon foot on bottom of each stationary Post adjusts easily for floor irregularities. Dunnage stand recommended for heavy usage with shelves 54" (137,2 cm) or longer. Increases capacity of bottom shelf to 1,000 lbs. (450 kg).

#### Optional Accessories

Includes Wall Fastener and Seismic Foot. Each are packed 4 per case. Identification Tags clip easily onto traverses.

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Code No. \_\_\_\_\_

Quantity \_\_\_\_\_



Four Shelf Add-On Unit consists of one Post Kit and four Vented Shelf Kits.



Dunnage Stand



Set of Left and Right Corner Connectors (1 set required per shelf).

### Approvals



Components

\* Does not include 6" (15 cm) Shelf Plate, Wall Fastener and Seismic Foot.

## Stationary - Add-On Units

### 4 Shelf Units, Vented Shelf Plates only

### Four shelf Add-On Unit includes one Post Kit and four Vented Shelf Kits

#### 64" (162,6 cm) Height 18" (45,7 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSA48366	36" 91,4	61.56 (5.90)	27,92 (0,1671)
CSA48426	42" 106,7	70.28 (5.90)	31,88 (0,1671)
CSA48486	48" 121,9	75.56 (5.90)	34,27 (0,1671)
CSA48546	54" 137,2	84.28 (5.90)	38,50 (0,1671)
CSA48606	60" 152,4	91.00 (5.90)	41,28 (0,1671)

#### 72" (182,9 cm) Height 18" (45,7 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSA48367	36" 91,4	61.91 (5.90)	28,08 (0,1671)
CSA48427	42" 106,7	70.63 (5.90)	32,04 (0,1671)
CSA48487	48" 121,9	75.91 (5.90)	34,43 (0,1671)
CSA48547	54" 137,2	86.03 (5.90)	39,00 (0,1671)
CSA48607	60" 152,4	91.35 (5.90)	41,44 (0,1671)

#### 64" (162,6 cm) Height 21" (53,3 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSA41366	36" 91,4	66.82 (7.17)	30,31 (0,2030)
CSA41426	42" 106,7	77.02 (7.17)	34,94 (0,2030)
CSA41486	48" 121,9	82.86 (7.17)	37,59 (0,2030)
CSA41546	54" 137,2	93.10 (7.17)	42,23 (0,2030)
CSA41606	60" 152,4	101.14 (7.17)	45,88 (0,2030)

#### 72" (182,9 cm) Height 21" (53,3 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSA41367	36" 91,4	68.57 (7.17)	31,10 (0,2030)
CSA41427	42" 106,7	78.77 (7.17)	35,73 (0,2030)
CSA41487	48" 121,9	84.61 (7.17)	38,38 (0,2030)
CSA41547	54" 137,2	94.85 (7.17)	43,02 (0,2030)
CSA41607	60" 152,4	102.89 (7.17)	46,67 (0,2030)

#### 64" (162,6 cm) Height 24" (61 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSA44366	36" 91,4	68.94 (8.50)	31,27 (0,2407)
CSA44426	42" 106,7	77.74 (8.50)	35,26 (0,2407)
CSA44486	48" 121,9	86.50 (8.50)	39,24 (0,2407)
CSA44546	54" 137,2	95.30 (8.50)	43,50 (0,2407)
CSA44606	60" 152,4	101.78 (8.50)	46,17 (0,2407)

#### 72" (182,9 cm) Height 24" (61 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSA44367	36" 91,4	70.69 (8.50)	32,06 (0,2407)
CSA44427	42" 106,7	79.49 (8.50)	36,06 (0,2407)
CSA44487	48" 121,9	88.25 (8.50)	40,03 (0,2407)
CSA44547	54" 137,2	97.05 (8.50)	44,00 (0,2407)
CSA44607	60" 152,4	103.53 (8.50)	46,96 (0,2407)

### Corner Connector Set

Case Pack: 1 set

code	description	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSCC	Right and Left	0.38 (0.04)	0,02 (0,07)

### Architect Specs

- Posts:** Internal steel core, reinforced polypropylene exterior.
- Post Connectors:** Reinforced polypropylene.
- Traverses:** Internal steel core, reinforced polypropylene exterior.
- Vented/Solid Shelf Plates:** Reinforced polypropylene with Camguard™ antimicrobial.
- Corner Connectors:** Reinforced nylon.
- Adjustable Foot:** Reinforced nylon.
- Seismic Foot:** Stainless steel post and wide foot plate, 3 holes for bolts. (Bolts not provided)
- Wall Fastener:** Stainless steel.

### Dunnage Stands

Case Pack: 1

#### 6 1/2" (16,5 cm) Height

code	width	case lbs. (cube)	case kg. (cube m <sup>3</sup> )
CSDS18	18"	2.90 (0.22)	1,30 (0,0062)
CSDS21	21"	3.10 (0.26)	1,40 (0,0074)
CSDS24	24"	3.30 (0.30)	1,50 (0,0085)

### Optional Accessories

- Seismic Foot** (Bolts not provided)  CSEQ3 **Color:** Silver **Case pack:** 4 each
- Wall Fastener**  CSWF **Color:** Silver **Case pack:** 4 each
- Identification Tag 6"**  CSID **Color:** White/Clear **Case pack:** 12 each
- Identification Tag 3"**  CSID3 **Color:** White/Clear **Case pack:** 12 each

### Standard Colors

- Speckled Gray (480)

### Approvals



**NSF Components**

\* Does not include 6" (15 cm) Shelf Plate, Wall Fastener and Seismic Foot.