

Blixer® 8

**A** SALES FEATURES

Blixer 8 is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B TECHNICAL FEATURES

Blixer 8. 3-phase. Power 3 HP. 2 speeds. Pulse function. 8 Qt. stainless-steel bowl with 2 handles. Bowl-base blade assembly with 2 detachable fine serrated blades included. Scraper arm and lid wiper included. 5 to 25 portions (7 oz.) and more.

Select your options at the back page, **F** part.

C TECHNICAL DATA

Output power	3 HP
Electrical data	208-240V/60/3
Speeds	1800 and 3600 rpm
Dimensions (HxLxW)	23 15/16" x 21 1/2" x 12 7/16" - Cube 3.73
Rate of recyclability	95%
Net weight	110 lbs
Nema #	L15-20P
Reference	BLIXER 8 - 208-240V/60/3

D

Number of 7 oz portions :

5 to 25 portions

Quantity processed per operation

2 to 11 lbs

E PRODUCT FEATURES / BENEFITS**MOTOR BASE**

- **Direct drive induction motor (no belt)** for intensive use.
- Power 3 HP.
- Stainless steel motor shaft.
- Flat, easy-clean motor base.
- IP65 control panel with flush buttons.
- Magnetic safety and motor brake.
- **2 speeds : 1800 and 3600 rpm**
- Pulse function for a better cut precision.

CUTTER FUNCTION

- 8 Qt. stainless-steel bowl with 2 handles for a better grip.
- Central bowl locking system for easy assembly.
- Bowl-base blade assembly with 2 fine serrated blades to ensure a perfectly uniform consistency, even when processing small quantity.
- Transparent lid to enable user to monitor processing.
- Opening in centre of lid for adding liquid or dry ingredients during processing.
- **Transparent lid with bowl scraper** to improve the end-product consistency and **with a lid wiper** to enable user to monitor processing.
- **Opening in center of lid** for adding liquid or dry ingredients during processing.

INCLUDED ACCESSORIES

- Stainless steel fine serrated blade assembly (2 blades)
- Scraper arm and lid wiper

STANDARDS

ETL electrical and sanitation Listed/ cETL (Canada)



Blixer® 8

F OPTIONAL ATTACHMENTS

- 2 Blade Fine Serrated Edge Stainless Steel Adjustable Blade Assembly - Ref. 27377
- Lid Assembly with seal - Ref. 59319
- Complete Bowl Assembly - Ref. 59264

G ELECTRICAL DATA

208-240V/60/3 – delivered with cord and plug.

