H5X® Element SST

Height: 28.5" Width: 7.4" Depth: 18.9" (72.4cm) (18.8cm) (48.0cm)



- LED display provides simple temperature adjustment
- Thinsulate® tank insulation provides increased energy efficiency
- Programmable "Energy Saver Mode" reduces operating cost during idle periods
- The perfect tool for added control over quality coffee and tea
- Contemporary, space-saving design
- Digital thermostat provides constant and accurate temperatures of 60°- 212°F (15.6°-100°C)

Agency:





Specifications

Product #: 43600.0002 Temp. Setting: 212°F (100.000°C)

Water Access: Plumbed Dispense: Pull & Hold

Finish: Stainless
Faucet: Upper

Additional Features

Electrical & Capacity

| Volts* | Amps | Watts | Cord Attached | Plug Type | 8oz cups/hr 236ml cups/hr | Input H ² O Temp. | Phase | # Wires plus Ground | Hertz |
|--------|------|-------|------------------|-----------|------------------------------|---------------------------------|-------|------------------------|-------|
| 208 | 19.5 | 4050 | No | - | - | 60°F (15.5°C) | 1 | 2 | 60 |

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements


| · · · · · · · · · · · · · · · · · · · | | | | | | | |
|---------------------------------------|---------|-------------------------|---------------------------|--|--|--|--|
| PSI | kPa | Fitting Supplied | Water Flow Required (GPM) | | | | |
| 20-90 | 138-621 | 1/4" Male Flare Fitting | - | | | | |


CAD Drawings


| 2D | Revit | KLC |
|----|-------|-----|
| • | | |


MARNING:











| Unit | | | | Shipping | | | | | |
|---------|----------|---------|----------|----------|----------|----------|------------|-----------------------|--|
| | Height | Width | Depth | Height | Width | Depth | Weight | Volume | |
| English | 28.5 in. | 7.4 in. | 18.9 in. | 32.9 in. | 11.0 in. | 20.7 in. | 32.500 lbs | 4.338 ft ³ | |
| Metric | 72.4 cm | 18.8 cm | 48.0 cm | 83.7 cm | 27.9 cm | 52.5 cm | 14.742 kgs | 0.123 m³ | |




Related Products & Accessories: H5X® Element SST(43600.0002)





Product #: 02545.0000



























Serving & Holding Options: H5X® Element SST(43600.0002)

Serving and Holding selections are currently unavailable. Please contact your sales representative to find out more information.

