

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Model # : Item # :

Qty :

Available W/H :

Approval :

Sandwich / Salad Unit

Food Prep Tables J Series

Model : JST-72





Convenient cutting board side rail

Our cutting board is 9-1/2" deep and 1/2" thick to provide ample working space, and is made of easy to use and sanitize LDPE (Low Density Polyethylene). The new side rail cutting board bracket makes it easy to secure and remove the cutting board and it accepts different sizes too (max. 1/2" thickness)

Hot gas condensate system

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

Side mount compressor unit

By positioning the compressor on the side of the unit, refrigerators can now be serviced without being moved. Our innovative, front breathing feature also allows this model to provide high efficiency in narrow spaces.

Efficient refrigeration system

Swing

Door

3

Turbo Air J series refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

Adjustable, heavy duty, PE(polyethylene) coated wire shelves

CU./FT.

18

#of

Pans

18

#of

Hood

2

HP

1/4

#of

Shelves

3

Exterior & interior of the cabinet

The Turbo Air J series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

Refrigerator holds 33°F ~ 39°F for the best in food preservation



Model

JST-72

* Depth does not include 1-1/2" for cutting boards and 1" for rear spacers. † Height does not include 5-7/8" for caster height.

Sandwich / Salad Unit

Model : JST-72

ELECTRICAL DATA	
Voltage	115/60/1
Plug Type	(i) NEMA 5-15P
Full Load Amperes	4.8
Compressor HP	1/4
Cord Length ft.	9
Refrigerant	R-134A
DIMENSIONAL DATA	
Ext. Length Overall in.	707/8 (1800mm)
Ext. Depth Overall in.*	271/2 (698mm)
Ext. Height Overall in. ⁺	353/4 (908mm)
# of Doors	3
# of Shelves	3
# of Pans	18
Net Capacity cu. ft.	18
Net Weight Ibs.	254
Gross Weight lbs.	275

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 1-1/2" for cutting boards and 1" for rear spacers.

* Depth does not include 1-1/2" for cutting boards and 1" for rear = † Height does not include 5-7/8" for caster height.

| Height does not include 5-778 for caster height.

WARRANTY : 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

- Self-contained system
- Standard 4" swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included
- 91/2" deep, ½" thick cutting board included
- 2.5" dia. casters available (optional) ½" diameter & 13 TPI
- Door locks available (optional)
- Legs available for all models (optional)


OPTIONAL ACCESSORIES :

- 2.5" Diameter casters
- 5" Diameter casters
- 6" ABS plastic legs


(II)

Intertek

Additional PE coated wire shelves



PLAN VIEW





Intertek

lurbo air

Turbo Air : 800-627-0032
GK : 800-500-3519
Warranty : 800-381-7770
AC : 888-900-1002

Food Prep Tables J Series

(GERMAN

