

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model #:	
Item #:	Qty:
Available W/H :	
Approval :	

Chef Base Refrigertor

Chef Bases PRO Series

Model: PRCBE-60R-N

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



= FEATURES & BENEFITS ==_

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

- Digital temperature display on front panel
- Strong body and durable construction

Built with heavy duty 16 ga. stainless steel, Chef Base top is manufactured of one-piece reinforced stainless steel to ensure durability.

Countertops

PRCBE-48/60R-N supports up to 788 pounds of equipment. PRCBE-72/84R-N supports up to 1,192 pounds of equipment.

- Durable stainless steel drawers
- Top is insulated to eliminate heat transfer to the interior of cabinet

Front breathing design for easy maintenance and zero-clearance installation

With compressors positioned on the side of the unit, our refrigerators can now be serviced without being moved. Our innovative, front breathing feature also allows this model to be highly efficient in narrow spaces.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Stainless steel top with Drip Guard (marine)
- Hot gas condensate system
- Full length drawer with gasket guard
- Drawer slider load capacity up to 180 lbs
- Magnetic snap-in gasket
- Refrigerator holds 33°F ~ 38°F for the best in food preservation













PRCBE-60R-N	2	9.77	127/8 x 20 x 6 (6)	1/4	3.2	372	60 x 331/2 x 215/8
Model	Drawers	CU./FT.	Pans Capacity (in.)	HP	AMPS	Crated Weight (lbs.)	L x D x H*

(unit: inch)

Chef Base Refrigertor

Model: PRCBE-60R-N

ELECTRICAL DATA	TRICAL DATA				
Voltage	115/60/1				
Plug Type	① NEMA 5-15P				
Full Load Amperes	3.2				
Compressor HP	1/4				
Cord Length (ft.)	9				
Refrigerant	R-290				
DIMENSIONAL DATA					
Ext. Length Overall (in.)	60 (1525mm)				
Ext. Depth Overall (in.)	331/2 (852mm)				
Ext. Height Overall (in.)*	21 _{5/8} (550mm)				
# of Drawers	2				
Pans Capacity (in.)(# of pans)	127/8 x 20 x 6 (6)				
Net Capacity (cu. ft.)	9.77				
Net Weight (lbs.)	317				
Gross Weight (lbs.)	372				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

STANDARD FEATURES


- · Anti-corrosion coated evaporator
- · Self-contained system
- 4" dia. swivel casters standard

■ OPTIONAL ACCESSORIES


- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- · Condensing unit on the right available
- * Please allow lead time for shipping. Please contact factory for more details.

PLAN VIEW


* Each drawer accommodates up to 6" deep sixth (1/6) size pans (drawer pans not included)



TOP VIEW



FRONT VIEW



SIDE VIEW

Ver.20190812





















■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002

^{*} Height does not include 5" for caster height.